

CLIMATROL WATER COOLERS



SIDWAL WATER COOLER IS NOW **CLIMATROL**



Climatrol Corporation is an ISO 9001:2015 certified privately held Indian company with a specialization in Design, Development & Manufacturing of Refrigeration Equipment and Drinking Water Coolers since 2009. Our expertise is solicited by a diverse range of industries dealing in Perishable Foods, Medicines, Chemicals, etc. where consistent temperature control is required.

We typically undertake Cold Room & Frozen Room projects involving PUF Panels and Refrigeration unit coolers for medium and low temperature applications.

Our in-house manufacturing capability of PUF Panels & Refrigeration Systems along with our robust designs for high ambient conditions prevalent in India are considered one of the best in the country.

Available from **15 ltr. to 400 ltr.**



8/15 BC



20/40



40/40



40/80

OUR CLIENTS



60/120



150/150



150 R



225/400

TECHNICAL

		SS-MODELS																	CS-MODELS																		
Particulars	Unit	8/15 BC	8/15	20/20 BC	20/20	20/40	40/40	40/80	60/80	60/120	80/120	150/150	150/400	170/400	225/400	40R	150R	300R	8/15 BC	8/15	20/20 BC	20/20	20/40	40/40	40/80	60/80	60/120	80/120	150/150	150/400	170/400	225/400	40R	150R	300R		
Cooling Capacity	Liters/hr	8	8	20	20	20	40	40	60	60	80	150	150	170	225	40	150	300	8	8	20	20	20	40	40	60	60	80	150	150	170	225	40	150	300		
Storage Capacity	Ltrs.	15	15	20	20	40	40	80	80	120	120	150	400	400	400	Pressure type	Pressure type	Pressure type	15	15	20	20	40	40	80	80	120	120	150	400	400	400	Pressure type	Pressure type	Pressure type		
Glass/ltrs at rated condition	Nos.	40	40	100	100	100	200	200	300	300	400	750	750	750	1125	200	750	1500	40	40	100	100	100	200	200	300	300	400	750	750	750	1125	200	750	1500		
Power Supply	Volt	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V	230V			
Rated Current	Amp.	0.9	0.9	1.5	1.5	1.5	2.0	2.8	2.7	3.9	6.0	7.8	7.8	7.8	10.5	2.8	7.8	11.9	0.9	0.9	1.5	1.5	1.5	2.0	2.8	2.7	3.9A	6.0	7.8	7.8	10.5	2.8	7.8	11.9			
Power Consumption	Watt.	150	150	180	180	180	450	575	600	775	900	1550	1550	1550	2100	575	1550	2450	150	150	180	180	180	450	575	600	775	900	1550	1550	2100	575	1550	2450			
Material		FULL BODY STAINLESS STEEL (304 GRADE)																	FRONT PANEL STAINLESS STEEL																		
Material of Tank	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	NO TANK	NO TANK	NO TANK	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	SS-304	NO TANK	NO TANK			
a) Chiller Tank		Stainless Steel																	Stainless Steel																		
b) Top Door		Stainless Steel																	Galvanised Steel																		
Front Panel "		Stainless Steel																	Stainless Steel																		
Top (tank cover)		Stainless Steel																	SS-304 SS-304 SS-304 SS-304 AL AL AL AL AL AL AL AL AL AL AL AL AL AL AL																		
Side Panel/Rear Panel		Stainless Steel																	Galvanised Steel																		
c) Drip Tray		Stainless Steel																	Stainless Steel																		
d) Bubble top attachment		Optional																	Optional																		
Faucets		Brass Chrome Plated																	Brass Chrome Plated																		
No.of Faucets (Taps)-Cold Water		01	01	01	01	01	01	02	02	02	02	02	04	04	04	01	01	01	01	01	01	01	01	01	02	02	02	02	04	04	04	01	01	01			
Legs		Nylon										SS-304			SS-304			SS-304			Nylon				SS-304			SS-304			SS-304			Nylon			
Compressor		Hermetically Sealed Reciprocating																	Hermetically Sealed Reciprocating																		
Refrigerant		R-134a / R-22																	R-134a / R-22																		
Unit Dimensions (mm)																																					
Width	W	300	300	350	350	435	435	480	480	715	715	853	870	870	870	425	610	815	300	300	350	350	435	435	480	480	715	715	853	870	870	870	425	610	815		
Depth	D	455	455	500	500	580	580	660	660	660	660	660	810	810	810	375	610	815	455	455	500	500	580	580	660	660	660	660	810	810	810	375	610	815			
Height	H	910	960	1025	1070	1160	1160	1160	1160	1285	1285	1285	1880	1880	1880	715	910	1125	910	960	1025	1070	1160	1160	1160	1285	1285	1285	1880	1880	1880	715	910	1125			
Net Weight	kg	23	26	34	36	45	45	47	53	64	85	88	137	137	155	36	77	123	23	26	34	36	45	45	47	53	64	85	88	137	137	155	36	77	123		



CLIMATROL
CORPORATION
QUALITY
REFRIGERATION
EQUIPMENT

+91 11 4077 5500
+91 98718 69666, +91 98188 81544
info@climatrol.in / salesupport@climatrol.in

Corporate: 108 A Madangir, New Delhi-110062
Factory: Main Thapal Indl. Area, Kala-Amb (Distt. Sirmour) H.P. - 173030
www.climatrol.in

